



Cidron Standard Reader

- SECURE ACCESS CONTROL



Secure Access Module

The Cidron reader features a contact card socket which is designed to read Secure Access Module's (SAM's), embedded on a SIM-card sized contact chip.



IP65

Cidron is a IP65 classified reader which has an operating temperature of $-40^{\circ} - +70^{\circ}\text{C}$.

The Cidron reader family is compatible with secure RFID-technologies incorporated in a robust, timeless design which making them ideally suited for both indoor- and outdoor installations in all kinds of physical access control applications.

Cidron Standard is a reader operating at 13.56MHz and supports reading for instance iCLASS UID, MIFARE Classic®, MIFARE Plus® sector, MIFARE Random UID or MIFARE® DESFire® application which allows for AES128 encrypted communication between credential and reader. Cidron Standard is versatile and can easily be configured to read up to two different card data objects and handles both 7-byte and 4-byte MIFARE UID's at the same time. This means that you can read credentials from different populations and it also gives the possibility of, in a controlled manner, upgrading from a less secure MIFARE Classic sector reading to a more secure MIFARE DESFire application.

The Cidron Standard is available both, with- or without keypad. The version with keypad has backlit keys which is configurable to be always on, off or in auto mode, which means that when a card is presented to the reader or a key is pressed the keypad will light up. The version without keypad has a symbol light at the front of the reader which will be lit when a card is presented to a reader, configured to auto mode.

Technical specifications



| Model Name | Standard PIN | Standard NO PIN | Slim PIN | Slim NO PIN | Combi PIN | Combi NO PIN |
|---------------------------------------|---|-----------------|---|-------------|---|--------------|
| »» Operating frequency | 13,56MHz | | | | 13,56MHz + 125kHz | |
| »» Reading technologies | MIFARE CSN 4 byte, MIFARE CSN 7 byte, MIFARE Classic, MIFARE Plus, MIFARE DESFire 0.6 and MIFARE DESFire EV1, MIFARE DESFire EV2 ¹ and MIFARE Random UID. ICLASS UID ISO14443B. Also supports other ISO 14443 A/B ² compatible cards. | | | | Electromarine EM4200. HID® Proximity. MIFARE CSN 4 byte, MIFARE CSN 7 byte, MIFARE Classic, MIFARE Plus, MIFARE DESFire 0.6 and MIFARE DESFire EV1, MIFARE DESFire EV2 ¹ and MIFARE Random UID. ICLASS UID ISO14443B. Also supports other ISO 14443 A/B* compatible cards. | |
| »» Secure Access Module | MIFARE SAM AV2, external SIM card connection slot. | | | | | |
| »» Reading output format | Wiegand, Clock/Data, OSDP 1, OSDP 2 (including Secure channel), RS232 and RS485. | | | | | |
| »» Reading output format | 24-1024 (excluding parity bits). | | | | | |
| »» Keypad output format | Wiegand 4bit, Wiegand 8bit (Dorado), Wiegand 26bit, OSDP ASCII format. | | | | | |
| »» Keypad | 12 digit keypad in 4 rows of 3 keys in each row. ³ | — | 12 digit keypad in 6 rows of 2 keys in each row. ³ | — | 12 digit keypad in 4 rows of 3 keys in each row. ³ | — |
| »» Indicators | LED, Green, Red and Yellow (Bi-color). Backlight in blue color. Buzzer. | | | | | |
| »» Power supply | 9 – 30VDC | | | | | |
| »» Current consumption | 24VDC idle mode with heater inactive 40-60 mA ⁴ 12VDC idle mode with heater inactive 50-90 mA ⁴ | | | | | |
| »» Input/Output | 4 input for LED and buzzer and 2 configurable input/output. | | | | | |
| »» Tamper alarm | Built-in mechanical tamperswitch which allows for indication both, break off protection and opening of the reader. | | | | | |
| »» Operating temperature | –40° – +70°C | | | | | |
| »» Heater | Thermostat controlled embedded heater. | | | | | |
| »» Operating humidity | 0 – 95% RHNC (Relative Humidity No Condensation) | | | | | |
| »» Ingress Protection Classification: | IP 65 (requires the accessory climate protection SC9901) | | | | | |
| »» Housing dimensions | L=109mm, H=25mm, W=79mm | | L=141mm, H=25mm, W=48mm | | L=109mm, H=25mm, W=79mm | |
| »» Configuration Methods | Configuration card, reader tool software or factory configured readers. | | | | | |

¹ Application coding must be in accordance with EV1.

² Not all ISO14443 B cards have been implemented in the reader, please contact Seriline for more details on current status. MIFARE is a registered trademark of NXP B.V. and is used under license.

³ With configurable backlight in blue color. Control features On/Off/Auto indicators. Light intensity can be adjusted.

⁴ Current consumption differs depending on functionality used and can also be limited in the reader configuration, please consult the Cidron Standard/Combi full installation guide for current consumption, before dimensioning power supply.